

NuREND PLUS Basecoat

DESCRIPTION

NuREND PLUS Basecoat is a polymer modified, cement based render manufactured for masonry surfaces. A thin coat applied to brick or other masonry substrates.

KEY BENEFITS

NuREND PLUS Basecoat is a product designed to be user friendly. Using a diamond float, the surface is finished evenly and ready for texture.

SURFACE PREPARATION & TEMPERATURES

Surface

- The surface to which this product is applied to should be clean, dry, stable, dirt and dust free, and able to receive a coating.

Temperatures

- During application, the temperature of the substrate should not be below 5°C or over 35°C.
- Protect freshly applied render from high wind, freezing, frost and temperatures below 5°C for 48 hours after application.
- The rendered surface should also be protected from rain for up to 24 hours after application.

APPLICATION

Care should be taken to ensure that NuREND PLUS Basecoat is thoroughly mixed, using a Mixing Drill in an appropriate vessel.

Mixing

- 2-4 litres of clean water (without additives) into a mixing vessel and, with the mixer in operation, add one full 20 kg bag of NuREND PLUS Basecoat and mix until the mix is well dispersed.
- Let the mixed contents stand for 5 minutes and give a further mix adding water or render if required to bring the mix to a creamy consistency.

Application

- Trowel on first coat area and immediately finish with a straight edge or float. Work the area until it is flat and even.
- Apply a second and subsequent coat, with each coat being no less than 2mm & up to minimum total thickness of no less than 5mm for both coats.
- Once the finish coat/s have firmed slightly, rub-up with a diamond float to produce an even, uniform and smooth surface.

DRYING & CURING

Drying and curing of the product is affected by porosity of the surface/substrate, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

- Touch Dry approx. 2 hours
- Hard Dry 12 to 24 hours
- Re-Coat when product is hard dry

However, If using a full acrylic topcoat (example Paint/Wet Texture) there must be no more than 12% moisture content in the surface at the time of coating (Approximately 7 - 28 days).

COVERAGE

Masonry	When applying 1 - 2 coats, at a total thickness of no less than 5mm	Approx. Coverage 5-7sqm per coat
---------	---	----------------------------------

Notes:

The theoretical coverage is based on this product applied in accordance with the Masonry Specification Sheet, which can be obtained by the manufacturer.

CLEAN UP

NuREND PLUS Basecoat should be cleaned from all tools and equipment with clean water immediately after use.

STORAGE

NuREND PLUS should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 - 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 6 months from the date of manufacture. If stored for longer than 6 months, product must be rechecked for suitability in the intended application.

PACKAGING & WEIGHT

Bag Material - Poly lined paper sack

Bag Contents - 20kg per bag

Pallet - 48 bags, total pallet weight 960 kg

GRADES

- FINE
- MEDIUM

HEALTH & SAFETY

Please consult the **Material Safety Data Sheet** and read the product packaging carefully before use. Material Safety Data Sheets are available by phoning **03 9544 8666**.

Conditions of Use and Disclaimer

The information contained in this Product Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

Whilst NuTex Coatings takes every care to ensure that any impurities in the Product are eliminated at the time of manufacture, components of the product are natural materials including sands or mineral earths which may occasionally result in minor visual blemishes, NuTex Coatings shall not be liable for any such blemishes.