

NuREND High Build Basecoat

DESCRIPTION

NuREND High Build Basecoat is a polymer modified, cement based render manufactured for masonry surfaces. It is primarily used as a high build product for masonry surfaces.

KEY BENEFITS

NuREND High Build Basecoat is a product designed to cover uneven brickwork, large rake joints and specifically designed as a lightweight high build product.

SURFACE PREPARATION & TEMPERATURES

Surface

- The surface to which this product is applied to should be clean, dry, stable, dirt and dust free, and able to receive a coating.

Temperatures

- During application, the temperature of the substrate should not be below 5° or over 35°.
- Protect freshly applied render from high wind, freezing, frost and temperatures below 5° for 48 hours after application.
- The rendered surface should also be protected from rain for up to 24 hours after application.

APPLICATION

Care should be taken to ensure that NuREND High Build Basecoat is thoroughly mixed, using a Mixing Drill in an appropriate vessel.

Mixing

- 2-4 litres of clean water (without additives) into a mixing vessel and, with the mixer in operation, add one full 18kg bag of NuREND High Build Basecoat and mix until the mix is well dispersed.
- Let the mixed contents stand for 5 minutes and give a further mix adding water or render if required to bring the mix to a creamy consistency.

The render will be usable for at least an hour depending on the air temperature, keep the bucket in the shade on warmer days (adding more water will not re-activate the render).

CLEAN UP

NuREND High Build Basecoat should be cleaned from all tools and equipment with clean water immediately after use.

STORAGE

NuREND High Build should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 - 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 6 months from the date of manufacture. If stored for longer than 6 months, product must be rechecked for suitability in the intended application.

PACKAGING & WEIGHT

Bag Material - Poly Lined Paper Sack

Bag Contents - 18Kg Per Bag

Pallet - 48 Bags, Total Pallet Weight 864 kg

DRYING & CURING

Drying and curing of the product is affected by porosity of the surface/substrate, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

- Touch Dry +/- 2 Hours
- Hard Dry 12 to 24 Hours
- Re-Coat when product is hard dry

A coat of NuREND PLUS is to be applied over this product to give the substrate a smooth finish, ready for to the final texture coat (as the polystyrene raw material used within this product may come through next coat).

COVERAGE

Masonry Surfaces	Apply 1 even coat to cover all rake joints and/or imperfections in the substrate	Approx. Coverage 2-4sqm per coat
<small>Notes:</small> <ul style="list-style-type: none"> The theoretical coverage is based on this product applied (at a thickness of 5mm) in accordance with the Masonry Specification Sheet, which can be obtained by the manufacturer. 		

HEALTH & SAFETY

Please consult the **Material Safety Data Sheet** and read the product packaging carefully before use. Material Safety Data Sheets are available by phoning **03 9544 8666** or our website www.nutex.com.au

Conditions of Use and Disclaimer

The information contained in this Product Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

Whilst NuTex Coatings takes every care to ensure that any impurities in the Product are eliminated at the time of manufacture, components of the product are natural materials including sands or mineral earths which may occasionally result in minor visual blemishes, NuTex Coatings shall not be liable for any such blemishes.