

NuTEX Dado Finish

DESCRIPTION

NuTEX Dado Finish is a premium quality (sand/ cement based) product. It has a smooth finish and looks something like smooth concrete.

NuTEX Dado finish is very durable and has a distinct design aesthetic and will produce a mottled distressed look brought about by the weather.

SURFACE PREPARATION & TEMPERATURES

Surface

- The surface to which this product is applied to should be clean, dry, stable, dirt and dust free, and able to receive a coating.

Temperatures

- During application, the temperature of the substrate should not be below 5°C or over 30°C.
- Protect freshly applied product from high wind, freezing, frost and temperatures below 5°C for 48 hours after application.
- The finish should also be protected from rain for up to 48 hours after application.

APPLICATION

Care should be taken to ensure that the bag contents are thoroughly mixed, using a Mixing Drill in an appropriate vessel.

Prime

- Apply 1 coat of Romano/Dado primer, allow 24 hrs before applying NuTEX Dado Finish.

Mixing

- 2-4 litres of clean water (without additives) into a mixing vessel and, with the mixer in operation, add one full 20kg bag and mix until the mix is well dispersed.
- Let the mixed contents stand for 5 minutes and give a further mix adding water or render if required to bring the mix to a creamy consistency.
- Apply 1st coat with a steel trowel ,2nd coat finish a with flexible steel trowel.

The mixed contents will be usable for up to an hour depending on the air temperature, keep the bucket in the shade on warmer days (adding more water will not re-activate the product).

Sealer

- For a water repellent protective coating apply Silicon sealer.

CLEAN UP

NuTEX Dado Finish should be cleaned from all tools and equipment with clean water immediately after use.

STORAGE

NuTEX Dado should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 - 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 6 months from the date of manufacture. If stored for longer than 6 months, product must be rechecked for suitability in the intended application.

PACKAGING & WEIGHT

Bag Material - Poly lined paper sack

Bag Contents - 20kg per bag

DRYING & CURING

Drying and curing of the product is affected by porosity of the surface/substrate, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

- Touch Dry - Approximately 4 Hours
- Hard Dry - 12 to 24 Hours

However, If over coating with a full acrylic product (E.g. NuSHIELD) there must be no more than 12% moisture content in the surface at the time of coating (Approximately 7 - 28 days).

PRODUCT RANGE

Grades

- Ultra Fine

COVERAGE

Dado	<ul style="list-style-type: none"> Apply 1st coat at a thickness between 1-2mm After approximately 30 minutes when the coating is still "green" apply the 2nd coat over the wall to achieve a desired flat smooth finish 	Approx. Coverage 8-12sqm
-------------	--	--------------------------

Notes:

- The theoretical coverage is based on this product applied at a thickness of 2mm.

HEALTH & SAFETY

Please consult the **Material Safety Data Sheet** and read the product packaging carefully before use. Material Safety Data Sheets are available by phoning **03 9544 8666**.

Conditions of Use and Disclaimer

The information contained in this Product Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

Whilst Nutex Coatings takes every care to ensure that any impurities in the Product are eliminated at the time of manufacture, components of the product are natural materials including sands or mineral earths which may occasionally result in minor visual blemishes, Nutex Coatings shall not be liable for any such blemishes.