

NuPRIME

Multi-purpose Acrylic Primer

DESCRIPTION

NuPRIME is a water based, multi-purpose acrylic primer used to create a greater bond between different materials. It has excellent moisture resistance, specifically formulated for application to high porosity surfaces.

SURFACE PREPARATION & TEMPERATURES

Surface

- The surface to which this product is applied to should be clean, dry, stable, dirt, oil and dust free, and be able to receive a coating.

Temperatures

- During application, the temperature of the substrate should not be below 7°C or over 32°C.
- Protect freshly applied texture from high wind, freezing, frost and temperatures below 7°C for 48 hours after application.

APPLICATION

This product is applied using a roller and brush. Commencing from the top of the working area down to the bottom. We recommend that brush & roll at the same time to avoid picture framing.

CLEAN UP

All tools and equipment should be cleaned with water immediately after use.

STORAGE

NuPRIME should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 - 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If stored for longer than 12 months, product must be rechecked for suitability in the intended application.

PACKAGING & SIZE

Pail Material – PVC Plastic

Pail Size – 15 Litres

DRYING & CURING

Drying and curing of the product is affected by porosity of the surface/substrate, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

Drying

- Touch Dry approximately 1 hour

Curing

- Substrates must not contain more than 15% moisture prior to application.

COVERAGE

5 – 7 Sqm/Per Ltr

Figures are a guide only. Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

PRODUCT RANGE

GRADES

- Smooth
- Anti-Slip

SUITABLE SUBSTRATES

NuPRIME is suitable for use over all currently prepared substrates including;

- Acrylic/Polymer Modified Basecoats
- Clay/Concrete Bricks and Blocks
- Hebel Powerpanel
- Painted/Glazed Brickwork
- Fibre Cement Sheet (FCS)
- Slab Edge & Concrete Tilt Panels
- Traditional Sand & Cement Renders

Please contact our office on **03 9544 8666** or visit our website **www.nutex.com.au** for substrate specifications.

HEALTH & SAFETY

Please consult the **Material Safety Data Sheet** and read the product packaging carefully before use. Material Safety Data Sheets are available by phoning **03 9544 8666**.

In case of emergency please call 1800 033 111

Conditions of Use and Disclaimer

The data provided within this Data Sheet is correct at the time of publication; however it is the responsibility of those using this information to check that it is current prior to specifying or using this product.

Nutex Coatings Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with this Product Data Sheet. Due to our policy of continuing product improvement, Nutex Coatings Pty Ltd reserves the right to change this Data Sheet without further notice.

Whilst Nutex Coatings takes every care to ensure that any impurities in the Product are eliminated at the time of manufacture, components of the product are natural materials including sands or mineral earths which may occasionally result in minor visual blemishes, Nutex Coatings shall not be liable for any such blemishes.