PATCH - Dry

Joint Patching Compound

DESCRIPTION

NuPATCH Dry is a pre-blended (cement based, polymer modified) patching compound, specially designed for setting joints on rigid substrates such as Fibre Cement Sheet.

SURFACE PREP. & TEMPERATURES

Surface

- The surface to which this product is applied to should be clean, dry, stable, dirt and dust free, and able to receive a coating.

Temperatures

- During application, the temperature of the substrate should not be below 5°C or over 35°C.
- Protect freshly applied render from high wind, freezing, frost and temperatures below 5° for 48 hours after application.
- The rendered surface should also be protected from rain for up to 24 hours after application.

APPLICATION

Care should be taken to ensure that the product is thoroughly mixed, using a Mixing Drill in an appropriate vessel.

Mixing

- 2-4 litres of clean water (without additives) into one full 18Kg bag of NuPATCH.
- let the mixed contents stand for 5 minutes and give a further mix adding water or render if required to bring the mix to a creamy consistency.

Embedding Mesh for Joints

- Do not force the mesh into the render, it should be just below the surface

CLEAN UP

Product should be cleaned from all tools and equipment with clean water immediately after use.

STORAGE

Product should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 - 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 6 months from the date of manufacture. If stored for longer than 6 months, product must be rechecked for suitability in the intended application.

PACKAGING & WEIGHT

Bag Material - Poly Lined Paper Sack

Bag Contents – 17kg Per Bag

DRYING & CURING

Drying and curing of the product is affected by porosity of the surface/substrate, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

- Touch Dry - Approximately 2 Hours
- Hard Dry 12 to 24 Hours
- Re-Coat when product is hard dry

However, If over coating with a full acrylic product (E.g. NuSHIELD) there must be no more than 12% moisture content in the surface at the time of coating (Approximately 7 - 28 days).

RECOMMENDED SUBSTRATES

NuPATCH is recommended for use over the following substrates;

- Fibre Cement Sheet (FCS)
- James Hardie D3 ComTex Panel
- Painted/Glazed Brickwork

Please contact our office on 03 **9544 8666** or visit our website **www.NuTex.com.au** for substrate specifications.

HEALTH & SAFETY

Please consult the **Safety Data Sheet** and read the product packaging carefully before use. Safety Data Sheets are available by phoning **03 9544 8666**.

Conditions of Use and Disclaimer

The information contained in this Product Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

Whilst NuTex Coatings takes every care to ensure that any impurities in the Product are eliminated at the time of manufacture, components of the product are natural materials including sands or mineral earths which may occasionally result in minor visual blemishes, NuTex Coatings shall not be liable for any such blemishes.