NuTex ROMANO RENDER

DESCRIPTION

NuTex ROMANO RENDER is a premium quality (cement based, polymer modified) 2 component render top coat. It has a fine sand suede finish.

KEY BENEFITS

NuTex ROMANO RENDER is very durable and has a distinct design aesthetic and will produce a mottled distressed look brought about by weathering.

SURFACE PREPARATION & TEMPERATURES

Surface

- The surface to which this product is applied to should be smooth, clean, dry, stable, dirt and dust free, and able to receive a coating of NuTex PRIMER prior to application of the ROMANO RENDER
- DO NOT apply to hot or saturated substrates.

Temperatures

- During application, the temperature of the substrate should not be below 5°C or over 30°C.
- Protect freshly applied product from high wind, freezing, frost and temperatures below 5°C for 48 hours after application.
- The finish should also be protected from rain for up to 48 hours after application.

APPLICATION

Care should be taken to ensure that the bag contents are thoroughly mixed, using a Mixing Drill in an appropriate vessel.

Mixing

- 1-2 litres of clean water plus 2 litres of NuBOND into a mixing vessel and, with the mixer in operation, add one full 20kg bag and mix until the mix is well dispersed.
- Let the mixed contents stand for 5 minutes and give further mix adding water or render if required to bring the mix to a creamy consistency.

The mixed contents will be usable for up to an hour depending on the air temperature, keep the bucket in the shade on warmer days (adding more water will not re-activate the product).

To assist in suction uniformity and prevent premature drying (burning) NuTex PRIMER must be applied before using NuTex ROMANO RENDER.

Apply NuTex ROMANO RENDER evenly with a steel trowel approximately 2-3mm thick. Work the surface with an appropriate float until smooth. Use a sponge or rubber float to finish rubbing in a circular motion. To minimise the appearance of joint lines always finish a complete wall on one application.

Every effort should be made to protect finished wall areas with plastic or waterproof sheeting for 4 hours to prevent damage.

NuTex ROMANO RENDER should be applied by experienced and qualified tradespeople.

CLEAN UP

NuTex ROMANO RENDER should be cleaned from all tools and equipment with clean water immediately after use.

STORAGE

NuTex ROMANO RENDER should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5-35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 6 months from the date of manufacture. If stored for longer than 6 months, product must be rechecked for suitability in the intended application.

DRYING & CURING

Drying and curing of the product is affected by porosity of the surface/substrate, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

- Touch Dry - Approximately 2 Hours
- Hard Dry - 12 to 24 Hours

PACKAGING & WEIGHT

Poly lined paper sack - 20kg

COVERAGE

NuTex PRIMER	- Apply 1 coat with a roller. Can be top coated when touch dry.	Approx. Coverage 5-7 m^2/Lt.
ROMANO RENDER plus NuBOND	- Apply 2 – 3 mm thick - Add 2 Lt / 20 Kg Bag	5-7m^2/Bag

Notes:

- The theoretical coverage is based on this product applied at a thickness of 2mm.

HEALTH & SAFETY

Please consult the **Safety Data Sheet** and read the product packaging carefully before use. Safety Data Sheets are available by phoning **03 9544 8666.**

WARNING

NuTex ROMANO RENDER, its staff, distributors or agents have no control over the handling, on site blending, or application and therefore cannot be held responsible for the outcome. The recommendations for the product are a guide. Any claims for damage or any other action implied or directed at NuTex ROMANO RENDER cannot be accepted. NuTex ROMANO RENDER should only be applied by experienced, competent tradespeople.

Conditions of Use and Disclaimer

The information contained in this Product Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

Whilst NuTex Coatings takes every care to ensure that any impurities in the Product are eliminated at the time of manufacture, components of the product are natural materials including sands or mineral earths which may occasionally result in minor visual blemishes, NuTex Coatings shall not be liable for any such blemishes.